

TRUCK-MOUNTED CONCRETE PUMP SYG5211THB 25C-10(SZ-EU)



Energy-saving

- Pump efficiency is increased up to 25% while fuel consumption is decreased by up to 10%.



Safety

- Our truck mounted concrete pump exemplifies Sany's precise, rigorous manufacturing philosophy and uncompromising focus on safety.



Highly Wear Resistant Parts

- The highly wear resistant parts improve efficiency and reduce down time.






Self-diagnosis Technology

- Continually monitors more than 200 aspects of the system during operation. Faults are displayed on the monitor. Review of the detected faults can reduce troubleshooting time by 70%.



TECHNICAL SPECIFICATION

Model			Unit	SYG5211THB 25C-10(SZ-EU)	
X-unit Spe.	Length		mm	8000	
	Width		mm	2490	
	Height		mm	3160	
	Dead weight		kg	12200	
Boom & Outrigger Specification	Vertical reach		m	24.7	
	Horizontal reach		m	21.1	
	Reach depth		m	11.7	
	Unfolded reach		m	6.2	
	1st Section	Length	mm	6670	
		Articulation		90°	
	2nd Section	Length	mm	5100	
		Articulation		180°	
	3rd Section	Length	mm	4390	
		Articulation		245°	
	4th Section	Length	mm	4955	
		Articulation		230°	
	Rotation			± 360°	
	Front outrigger spread L-R		mm	5200	
	Rear outrigger spread L-R		mm	3440	
Pumping System Specification	Output		m³/h	137	
	Pressure		MPa	6	
	Max. strokes per minute		times/min	34	
	Delivery cylinder diameter		mm	230	
	Stroke length		mm	1600	
	Hydraulic system			Open	
	Hydraulic system oil pressure		MPa	32	
	Oil tank capacity		L	320	
	Water tank capacity		L	300	
	Pipeline size		mm	125	
	End hose length		m	3	
	End hose diameter		mm	125	
	Chassis Specification	Chassis brand			/
		Chassis model			/
		Engine type			/
Engine maximum net power		kW/rpm	/		
Emission standard			/		
Capacity of fuel tank		L	/		
Displacement		L	/		
Max. speed		km/h	/		



www.sanyglobal.com

SANY Industrial Park, Economic and Technological Development Zone,
Changsha, Hunan, China, 410100
Sales Hotline
Tel: 0086-731-85835199
Mail: sales@sanyglobal.com

Service Hotline
Tel: 0086-4006098318
Mail: CRD@sany.com.cn

The product configuration (including technical parameters) is subject to change and the delivered actual machine without notice.