



# SSR120HT SINGLE DRUM ROLLER



## Extended life time

- ◆ The use of water wheel type lubrication on the vibratory bearing extends the bearing life up to 5,000 hours.
- ◆ Double filtration of engine high intake air, the hydraulic system contains three stage filtration.

## High efficiency

- ◆ 10% greater excitation force than other products in the same category resulting in 16.7% greater production.

## Operator comfort

- ◆ Cab mounted on vibration damping mounts
- ◆ Cab temperature control
- ◆ Operator control forces have been reduced

## Safety features

- ◆ Rounded bumpers front and rear
- ◆ Large rear glass and sloped hood for greater visibility

## Technical specifications


Model		SSR120HT
Load	Operating mass (kg)	12000
	Mass allocated to vibrating drum (kg)	7000
	Mass allocated to driving axle (kg)	5000
	Static linear load of vibrating drum (N/cm)	329
Compaction	Vibration frequency (Hz)	32/36
	Nominal amplitude (mm)	1.8/0.9
	Centrifugal force (kN)	280/178
	Diameter of vibrating drum (mm)	1500
	Width of vibrating drum (mm)	2130
	Vibrating drum rim thickness (mm)	25
Maneuverability	Travel speed (km/h)	0~7
		0~9
		0~4
		0~5.5
	Theoretical gradeability	55% / 60%
	Min. ground clearance (mm)	480
	Wheelbase (mm)	3023
	Steering angle (° )	± 35
	Swing angle (° )	± 12
	Min. turning outer diameter (mm)	11915
	Tire specification	23.1-26-14PR
Engine	Brand	Cummins
	Model	QSB4.5
	Emission	T4f
	Rated power (kW)	119
Capacities	Battery (V × Ah)	24 × 120
	Fuel tank (L)	200
	Hydraulic oil tank (L)	120

## Standard configurations

Config.	Systems	Description	Qty	Details		Remarks
Standard confi.	Main machine	SSR120HT single drum roller, standard	1	1. Engine 2. Travel pump 3. Vibration pump 4. Travel motor 5. Vibration motor 6. Reduction gears 7. Operating platform 8. Vibratory drum (Smooth)	9. Electrical system 10. Operating system 11. Front frame 12. Rear frame 13. Covering part 14. Rear axle assembly 15. Center articulated frame 16. Cab+Air Con	
	Shed	Shed	1	Low cost		Optional
Optional confi.	Vibratory drum with welded pad foot	Drum with welded pad foot	1	Vibratory drum with welded pad foot, which cannot be removed, suitable for compaction of clay, semi-clay, rocks, gravels, expansive soil, and coal cinder base		Substitute smooth drums permissible
	Vibratory drum with assembled pad foot	Drum with assembled pad foot	1	Vibratory drum with assembled pad foot, which can be removed to form a smooth drum; suitable for compaction of clay, semi-clay, rocks, gravels, expansive soil, and coal cinder base		Optional

## Dimensions

Size code	SSR120HT
A(mm)	3023
W(mm)	2240
L(mm)	5875
D(mm)	1500
H(mm)	3390
B(mm)	2130
K(mm)	480



### SANY HEAVY INDUSTRY CO. LTD.

SANY Industrial Park, Economic and Technological Development Zone, Changsha, Hunan, China, 410100  
 Sales Hotline  
 Tel: 0086-731-85835199  
 Mail: sales@sanyglobal.com

Service Hotline  
 Tel: 0086-4006098318  
 Mail: CRD@sany.com.cn

The product configuration (including technical parameters) is subject to change and the delivered actual machine without notice.

[www.sanyglobal.com](http://www.sanyglobal.com)