



SSR220AC-8H SINGLE DRUM ROLLER



Extended life time

- ◆ The use of water wheel type lubrication on the vibratory bearing extends the bearing life up to 5,000 hours.
- ◆ Double filtration of engine high intake air, the hydraulic system contains three stage filtration.

High efficiency

- ◆ 10% greater excitation force than other products in the same category resulting in 16.7% greater production.

Operator comfort

- ◆ Cab mounted on vibration damping mounts
- ◆ Cab temperature control
- ◆ Operator control forces have been reduced

Safety features

- ◆ Rounded bumpers front and rear
- ◆ Large rear glass and sloped hood for greater visibility

Technical specifications


Model		SSR220AC-8H
Load	Operating mass (kg)	22000
	Mass allocated to vibrating drum (kg)	11000
	Mass allocated to driving axle (kg)	11000
	Static linear load of vibrating drum (N/cm)	516
Compaction	Vibration frequency (Hz)	29/35
	Nominal amplitude (mm)	1.9/0.95
	Centrifugal force (kN)	390/258
	Diameter of vibrating drum (mm)	1600
	Width of vibrating drum (mm)	2130
	Vibrating drum rim thickness (mm)	40
Maneuverability	Travel speed (km/h)	0~5
		0~8
	Theoretical gradeability	30%
	Min. ground clearance (mm)	440
	Wheelbase (mm)	3185
	Steering angle (°)	± 35
	Swing angle (°)	± 12
	Min. turning outer diameter (mm)	12350
	Tire specification	20.5-25-16PR
Engine	Brand	Weichai
	Model	WP6G200E331
	Emission	China III
	Rated power (kW)	147
Capacities	Battery (V × Ah)	24 × 120
	Fuel tank (L)	300
	Hydraulic oil tank (L)	100

Standard configurations

Config.	Systems	Description	Qty	Details		Remarks
Standard confi.	Main machine	SSR220AC-8H single drum roller, standard	1	1. Engine 2. Travel pump 3. Vibration pump 4. Travel motor 5. Vibration motor 6. Operating platform 7. Vibratory drum (Smooth) 8. Electrical system	9. Operating system 10. Front frame 11. Rear frame 12. Covering part 13. Rear axle assembly 14. Center articulated frame 15. Cab+Air Con	
	Shed	Shed	1	Low cost		Optional
Optional confi.	Vibratory drum with welded pad foot	Drum with welded pad foot	1	Vibratory drum with welded pad foot, which cannot be removed, suitable for compaction of clay, semi-clay, rocks, gravels, expansive soil, and coal cinder base		Substitute smooth drums permissible
	Vibratory drum with assembled pad foot	Drum with assembled pad foot	1	Vibratory drum with assembled pad foot, which can be removed to form a smooth drum; suitable for compaction of clay, semi-clay, rocks, gravels, expansive soil, and coal cinder base		Optional

Dimensions

Size code	SSR220AC-8H
A(mm)	3185
W(mm)	2318
L(mm)	6620
D(mm)	1600
H(mm)	3330
B(mm)	2130
K(mm)	440



SANY HEAVY INDUSTRY CO. LTD.

SANY Industrial Park, Economic and Technological Development Zone, Changsha, Hunan, China, 410100
 Sales Hotline Tel: 0086-731-85835199
 Mail: sales@sanyglobal.com
 Service Hotline Tel: 0086-4006098318
 Mail: CRD@sany.com.cn

The product configuration (including technical parameters) is subject to change and the delivered actual machine without notice.

www.sanyglobal.com