


TRUCK-MOUNTED CONCRETE PUMP SYM5445THB 560C-8



Highly Reliable

- SANY has World-class lighthouse factories with top-level manufacturing capability, assuring reliable quality.
- Careful matching of components ensures stable performance of the whole machine.



Strong Pumping

- Single-button high/low pressure switch
- Multiple upgrades assure high suction rate
- Significant advantage in pumping efficiency



Extremely Economical

- The industry-leading longest service life of wear parts
- Advanced fuel combustion technology
- Targeted upgrades for different working conditions



Ultimate User Experience

- Comfortable cab comparable to passenger car experience
- Multi-language human-machine interface
- Easy-maintenance



TECHNICAL SPECIFICATION

Model		SYM5445THB 560C-8
Overall Spec.	Length (mm)	14270
	Width (mm)	2550
	Height (mm)	4000
	Dead weight (kg)	43600
Boom & Outrigger Specification	Vertical reach (m)	56
	Horizontal reach (m)	51
	Reach depth (m)	36.6
	Unfolding reach (m)	15.2
	1st Section	Length (mm)
		11390
	2nd Section	Articulation
		89°
	3rd Section	Length (mm)
		9230
	4th Section	Articulation
		180°
	5th Section	Length (mm)
		8750
	6th Section	Articulation
		180°
	7th Section	Length (mm)
		11070
	8th Section	Articulation
		240°
Pumping System Specification	Output (m³/h)	Low-pressure
		180
	Pressure (MPa)	High-pressure
		125
	Max. strokes per minute	Low-pressure
		8.3
	Delivery cylinder diameter (mm)	High-pressure
		12
	Stroke length (mm)	Low-pressure
		29
	Hydraulic system	High-pressure
		19
	Hydraulic system oil pressure (MPa)	Open
		260
	Oil tank capacity (L)	2100
		32
Chassis Specification	Water tank capacity (L)	610
		600
	Pipe diameter (mm)	125
		3
	End hose length (m)	125
		3
	End hose diameter (mm)	125
		125
	Chassis brand	SANY
		SYM5440THB1E
	Chassis model	D12C5-490E0
		348/1900
	Engine type	China stage V
		600
	Engine maximum net power (kW/rpm)	12.12
		90
	Emission standard	
	Fuel tank capacity (L)	
	Displacement (L)	
	Max. speed (km/h)	

Note: Cab colour and Product configuration will be subject to the actual factory configuration.



www.sanyglobal.com

SANY Industrial Park, Economic and Technological Development Zone,
Changsha, Hunan, China, 410100
Sales Hotline
Tel: 0086-731-85835199
Mail: sales@sanyglobal.com

Service Hotline
Tel: 0086-4006098318
Mail: CRD@sany.com.cn

The product configuration (including technical parameters) is subject to change and the delivered actual machine without notice.