



# BHL95

Engine power

74kW/2200rpm

Bucket capacity

0.2-1.0 m<sup>3</sup>

Operating weight

9200kg



Excellent performance



Excellent operability



With multiple functions



Comfortable driving

- ◆ Equipped with a powerful engine, more power; low fuel consumption, reducing operating costs.
- ◆ The precise excavation system based on anti-yaw technology works more accurately; the front and rear pilot controls are the top configuration in the industry.
- ◆ Equipped with a telescopic stick, multiple attachments can be switched at will, making it easy to cope with various complex working conditions.
- ◆ The spacious cab brings a comfortable driving experience, and the air suspension seats, heating and cooling air conditioning, LCD screen, and storage compartments bring a home-like feeling.

# Technical specifications

Specification		Main performance	
Operating weight	9200kg	Hydraulics	Load Sensing with Pilot Controls
Engine	Cummins	Main Hydraulic Pump	Kawasaki Variable Displacement —Axial Piston
Mode	QSF3.8	Hydraulic Power	39 Kw/2200 rpm
Engine standard	Tier3	System Flow	156 l/min
Type	4-stroke, water-cooling, mechanical type direct spraying	Operating Pressure	24.9 Mpa
Engine power	74kW/2200rpm	One-way Aux Line Max Flow	max 140 l/min
Maximum torque	420Nm/1600rpm	One-way Aux Line Max Pressure	16 Mpa
Displacement	3.8 L	Transmisio	ZF 4WD — 4 Speed Forward/Reverse
Bucket Breakout Force—Excavator	55 kN	Speed Gear 1	4.8 km/hr
Bucket Breakout Force—Loader	50 kN	Speed Gear 2	9.6 km/hr
		Speed Gear 3	19.3 km/hr
		Speed Gear 4	35.4 km/hr

## Machine dimensions

Overall dimensions(mm)	BHL95
A. Overall Length, Transport	5920
B. Overall Width, Transport	2280
C. Cab Roof Height	3129
D. Transport Height	3732
E. Ground Clearance	320
F. Length from Axle to Axle	2245
G. Total kingpost travel	1100
H. Turning Radius, Front Tires	4240
I. Turning Radius, Front Bucket	4800

Operation range(mm)	BHL95
L. Maxdimum Reach from Center of Swing Pivot	6644
M. Maximum Digging Depth	5366
N. Maximum Height to Bucket Hinge Pin	3478
O. Dump Clearance	>2700
P. Reach at Dump Position	>730
Q. Maxcimum Digging Depth with Bucket Leveled	88
R. Bucket Rollback Angle @ Ground Level	40
S. Bucket Rolback Angle @ Full Height	51
T. Loader Dump Angle @ Full Height	44
U. Maximum Operating Height	4293

