
QUALITY CHANGES


SANY Emergency Rescue Equipment

## Technical parameters

Item	Parameter				
Chassis model (imported)	Bentz	z Actro	s 3344	Fire control pump	Imported water pump
Total mass (t)	33.4			Fire control gun	Imported water gun
Maximum power (kw)	320			Getting on action time (s)	≤150
Specific power	9.5 11800×2500×3980			Getting off action time (s)	≤30
Outline of the whole vehicle (mm)				Fire control pump flow (L/s)	90
Boom structure	5+2+1			Flow of fire control gun (L/s)	60
Working height (m)	55			Jetting range of fire control gun (m)	≥65
Working amplitude (m)	23	25	27	Allowable lifting weight of basic boom (t)	2
Load of working bucket (kg)	500	320	130	Swing angle of working bucket	±45°



Dimensional diagram of product



Full-support dimensional diagram




QUALITY CHANGES THE WORLD



# DG55 Elevating Platform Fire Truck











- SANY 55m elevated platform fire truck is developed for rescue and fire control and fire extinguishment tasks at height of current high-rise buildings in cities, which effectively meets the fire control and rescue demands of 18-storey residential houses in cities.
- The reliable, efficient and intelligent design concept runs through each component of product, which makes it leading among similar products of the industry from it is born.

# Rescue

### Large scope

Maximum working amplitude: ≥27m

Maximum working height: ≥ 55m



### **Small site**

Length of whole vehicle:

≤20m Turning diameter:

Single-side support: ≤5.15m





### **Heavy load**

Maximum load of working bucket: ≥500kg

Lifting weight of basic boom: ≥2t






Scaling ladder, the scaling ladder can bear 6 people at most.
















rescue depth reaches 50m.



### Super intelligent

Intelligent boom control


Realize vertical displacement and horizontal displacement of working bucket with one key.

Intelligent rescue control

The memory function and action playback function of rescue working path realizes multiple times of rescue in fixed point.

Intelligent leveling control of working bucket

Leveling angle of working bucket ≤2°



SANY Emergency Rescue Equipment

### High reliability

Integrating more than 20 safety protection technology and

boom redundant control technology



# Fire extinguishment

### Large-flow fire extinguishment

Fire control system flow 60L/s







