





SYG5443THBCS 530C-10 TRUCK-MOUNTED CONCRETE PUMP

Energy-saving

Pump efficiency is increased up to 25% while fuel consumption is decreased by up to 10%.

Safety

Our C10 series truck mounted concrete pump exemplifies Sany's precise, rigorous manufacturing philosophy and uncompromising focus on safety.

Highly Wear Resistant Parts

The highly wear resistant parts improve efficiency and reduce down time.

Self-diagnosis Technology

Continually monitors more than 200 aspects of the system during operation. Faults are displayed on the monitor. Review of the detected faults can reduce troubleshooting time by 70%.



TECHNICAL SPECIFICATION

Model		lel	SYG5443THBCS 530C-10
u C	Length(mm)		14150
Overall Specification	Width(mm)		2550
	Height(mm)		4000
	Dead Weight(kg)		43400
Boom & Outrigger Specification	Vertical Reach(m)		53.5
	Horizontal Reach(m)		48.5
	Reach Depth(m)		34
	Min. Unfolded Reach(m)		15.2
	1st Section	Length(mm)	11390
		Articulation(°)	89
	2nd Section	Length(mm)	9230
		Articulation(°)	180
	3rd Section	Length(mm)	8750
		Articulation(°)	180
	4th Section	Length(mm)	9845
		Articulation(°)	240
	5th Section	Length(mm)	6860
		Articulation(°)	210
	6th Section	Length(mm)	3350
		Articulation(°)	110
	Rotation(°)		±360
	Front Outrigger Spread L-R(mm)		9470
	Rear Outrigger Spread L-R(mm)		12530
Chassis Specification Pumping System Specification	Output (m³/h)	Low-Pressure	200
		High-Pressure	137
	Pressure (MPa)	Low-Pressure	8.3
		High-Pressure	12
	Max. strokes per minute (times/min)	Low-Pressure	33
		High-Pressure	22
	Delivery Cylinder Diameter(mm)		260
	Stroke Length(mm)		2100
	Hydraulic System		Open
	Hydraulic System Oil Pressure(MPa)		32
	Oil Tank Capacity(L)		610
	Water Tank Capacity(L)		600
	Pipe Diameter(mm)		125
	End Hose Length(m)		3
	End Hose Diameter(mm)		125
	Chassis Brand		SANY
	Chassis Model		SYM5440THB1C
	Engine Type		D12C3-490E0
	Engine Maximum Net Power(kW/rpm)		348/1900
	Emission Standard		Euro III
	Fuel Tank Capacity(L)		600
	Displacement(L)		12.12
	Max. Speed(km/h)		90





