Vacuum Cleaning & Sewage Suction Truck





Ultra-High Water Pressure, Stain-Free Cleaning

- Equipped with an ultra-high pressure water pump to achieve large flow and high pressure operation, suitable for industrial cleaning of stubborn stains.
- 60-meter high-pressure rubber hose reel with cleaning nozzles, applicable for internal wall cleaning of long pipelines.






Vacuum Sewage Suction, Easy Maintenance

- Explosion-proof Roots vacuum pump with high vacuum, low energy consumption, adaptable to various materials, efficient and safe.
- Equipped with cyclone tank reverse suction and selfcleaning device, preventing clogging, extending filter service life, and enhancing material adaptability.





Off-Road Chassis, Excellent Passability

- Optional 6×6 off-road chassis, adaptable to more complex road conditions, with a maximum load capacity of 32t.
- Full-power power take-off (PTO) with sufficient power and easy switching.






Large Tank Capacity, Higher Safety

- Sewage tank volume of 14m³, with strong loading capacity.
- ADR-certified tank with positive/negative pressure overload protection and anti-leakage protection during tipping, ensuring higher safety.





Vacuum Cleaning & Sewage Suction Truck



Parameter Table

Category	Name	Vacuum Cleaning & Sewage Suction Truck
Whole Vehicle	Chassis Drive Mode	6×4(6×6 Optional)
	Emission Standard	Euro III and Above
	Wheelbase (mm)	5700+1370 (1400)
	Overall Dimensions (mm)	11300×2550×3990
	Sewage Tank Volume (m³)	13 -15
	Clean Water Tank Volume (m³)	≥2
Vacuum System	Maximum Air Volume (m³/h)	≥3500
	Maximum Vacuum Degree (%)	≥85
Water Washing System	Maximum Pressure (MPa)	50
	Maximum Flow Rate (l/min)	74

Project Cases



