SYL1800DC1

Unit Parameters


Model	SYL1800DC1
Frequency (Hz)	50
ESP (kW/kVA)	1980/2475
Rated Power (kW/kVA)	1800/2250
Rated Voltage (V)	400
Phase	3
Speed Control Type	Electronic speed control

Unit Size and Weight

Length (mm)	14500
Width (mm)	3500
Height (mm)	3500
Net Weight (kg)	30000


☑






☐





☐





* The above is for reference only, the actual size and weight are subject to the final design drawings.

SYL1800DC1

Engine

Brand		HUNAN DEUTZ
Model		D76S3
No. of Cylinders		16
Displacement (L)		76.3
Bore × Stroke (mm)		170×210
Starter Voltage (V)		24
Fuel Consumption (L/h)	100% load	477
	75% load	348
	50% load	239
	25% load	142

Alternator

Brand	Leroy Somer
Model	LSA 52.3 L9
Mode of connection	Three phases and four lines
Connection type	Y-shaped connection
Exciter system	AREP
Voltage regulator	D550
Bracket type	Single bearing

Controller

Brand	SANY
Model	SYGCU6110

Generator



SANY

SYL1800DC1

Configurations

“☑” configuration items	“☐” No configuration items	
Standard configuration	Optional configuration	
☑Engine	☑Fuel-water separator	☐Pre-lubrication system
	☐Water jacket heater	☐Inlet air shutdown valve
	☐Engine oil heater	☐Gas start system
	☐Heavy-duty air cleaner	
☑Alternator	☐Permanent magnet generator	☐Stator temperature sensor
	☑Digital voltage regulator	☐Bearing temperature sensor
	☐Anti-condensation heater	☐Differential protection
☑Single-machine control	☐Parallel control	☐Redundancy control
	☐Grid-connected control	☐Remote monitoring system
☐40℃ Radiator	☑50℃ Radiator	☐Customized radiator
☑Unit integrated output	☐Individual output cabinet	
☑Battery negative switch ☑Maintenance-free lead-acid battery and cable	☑Battery charger	
☑Industrial muffler	☐Residential muffler	☐Fire extinguishing muffler
☐No fuel tank	☐Chassis tank	☑Daily-use fuel tank
☑Rubber damper	☐Spring bumper	
☑Steel chassis	☐Silent box type noise reduction box	☑Container type noise reduction box
	☐Tool kit	

***Special instructions:**

The Rated power is the maximum power that a unit can operate continuously with variable load under standard environmental conditions, and is allowed to operate at an overload of 10% for 1 hour every 12 hours.

ESP refers to the maximum power that a generator set can operate continuously at variable loads under standard working conditions. The power of the generator set has been adjusted to its maximum, therefore overloading operation is not allowed.

***Operating conditions and power correction:**

Altitude: ≤ 1000m (power correction required when＞1000m).

Environmental temperature: 40 ℃ (Rated power correction required when ＞40 ℃, ESP power correction required when ＞25 ℃).

Relative humidity: ≤ 60%.

Land use.

Fixed on the ground during power supply to prevent movement.

When the operating conditions of the generator set do not meet the above conditions, the generator set needs to meet user needs through optional configurations, and the rated power value of the generator set needs to be corrected under high altitude and high temperature conditions.